OSHA Hazard Communication Standard 29 CFR 1900.1200 Prepared to GHS Rev. 4



SAFETY DATA SHEET

SECTION 1- CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: ProClean Acid Wheel Cleaner (SuperBright)

Product Use: Aluminum Cleaner, Brightner and Deoxidizer

Use Restrictions: For Industrial and Professional Use Only

Manufacturer: Ultra-Look Corp.

3903 Progress Drive Lakeland, FL 33811 Phone: 863-607-6700

Transportation Emergency: 800-535-5053 (INFOTRAC)

SECTION 2- HAZARDS IDENTIFICATION

1) GHS Classification of the substance or mixture:

Corrosive to metals- Category 1 Acute toxicity, Inhalation- Category 2 Acute toxicity, Dermal- Category 1 Acute toxicity, Oral- Category 2 Serious eye damage- Category 1 Skin Corrosion-Category 1A

2) Label Elements:



Signal Word: Danger

Hazard Statements:

H290- May be corrosive to metals

H300+H310+H330- Fatal if swallowed, in contact with skin or if inhaled.

H314- Causes severe skin burns and eye damage

H318- Causes serious eye damage

H335- May cause respiratory irritation

Precautionary Statements:

- P102- Keep out of reach of children
- P260- Do not breathe fume/mist/vapors/spray
- P262- Do not get in eyes, on skin, or on clothing
- P264- Wash skin thoroughly after handling
- P270- Do not eat, drink or smoke when using this product.
- P280- Wear protective gloves/protective clothing/eye protection/face protection.
- P284- Wear respiratory protection.

Response Statements:

P303+P353+P361+P363- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338+P310- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present, and easy to do so. Continue Rinsing. Immediately call a POISON CENTER of doctor/physician.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P310+P330+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Rinse mouth. Do NOT induce vomiting.

Storage and Disposal Statements:

P405- Store locked up.

P501- Dispose of contents/container in accordance with local/regional/national regulation.

Other Hazards:

OSHA HCS 2012- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

SECTION 3- COMPOSITION/INFORMATION ON INGREDIENTS

Chemical/Common Name	CAS #	PERCENTAGE	HAZARDOUS
Hydrofluoric Acid	7664-39-3	1-10%	Yes
Sulfuric Acid	7664-93-9	10-20%	Yes
2-Butoxyethanol	111-76-2	1-2%	Yes

SECTION 4- FIRST AID MEASURES

Inhalation: If affected, remove individual to fresh air. If breathing is difficult administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet and obtain medical attention.

Skin: Immediately flush affected area with lots of water for at least 2 minutes. Remove contaminated dothing and wash before reuse. Consult a physician.

Eyes: Flush immediately with large quantities of running water for at least 5 minutes. Obtain medical attention.

Ingestion: Immediately give a lot of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain immediate medical attention.

SECTION 5-FIRE FIGHTING MEASURES

Flash Point: None to boiling

Autoignition Temperature: Non combustible

Lower Explosive Limit: N/A Upper Explosive Limit: N/A

General Hazards-

Fire: Product is not flammable or combustible.

Suitable Extinguishing Media: As required to fight surrounding fire.

Fire Fighting Procedures: Wear self contained breathing apparatus for fire fighting if necessary.

Unusual Fire and Explosion Hazards: None known Hazardous Combustion Products: None known

SECTION 6- ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering.

Environmental precautions: Avoid run off to waterways and sewers.

Methods and material for containment and cleaning up: Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste disposal container.

SECTION 7- HANDLING AND STORAGE

Precautions for safe handling:

Avoid contact with skin and eyes by wearing protective clothing and equipment. Avoid inhalation of vapor or mist. Use only with adequate ventilation.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place. Store away from acids, acidic materials and oxidizers.

SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters:

Component	CAS #	ACGIH Exposure Limits	OSHA Exposure Limits
Sulfuric Acid	7664-93-9	0.2 mg/m3	1 mg/m3
2-Butoxy Ethanol	111-76-2	25 ppm	50 ppm
Hydrofluoric Acid	7664-39-3	0.5 ppm	6 ррт

Personal Protective Equipment-

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Hand protection: Wear protective gloves made from the following materials- nitrile rubber or polyethylene. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye Protection: Wear safety glasses with side shields.

Skin and Body Protection: Where extensive dermal exposure may be expected, either a chemical suit or chemical apron will be needed.

Hygienic Practices: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear Liquid Odor: Sharp N/D Odor Threshold: **Melting Point:** N/D Solubility in Water: Complete **Boiling Point:** 230°F Specific Gravity (WATER=1): 1.09 Vapor Pressure (mmHg): N/D Vapor Density (AIR=1): N/D

Evaporation Rate (WATER=1): Approaches water

Flash Point (C.O.C.): None pH (1% w/w in water): 1.0-1.5

SECTION 10- STABILITY AND REACTIVITY DATA

Reactivity: No data available

Stability: Stable under recommended storage conditions.

Material to Avoid: Avoid contact with alkalis and strong oxidizers such as permanganate, chlorine, ect.

Hazardous Polymerization: Will not occur Hazardous Decomposition Products: None

SECTION 11- TOXICOLOGICAL INFORMATION

Sulfuric Acid 93% (CAS 7664-93-9)-

Acute Toxicity: Harmful if inhaled. May cause respiratory irritation.

Acute oral toxicity- LD50 Oral: 2,296 mg/kg

Species: rat

Remarks: Ingestion causes burns to gastrointestinal tract.

Acute inhalation toxicity- LC50: ~ 510 mg/kg

Species: rat

Remarks: Exposure to mist causes severe burns to respiratory system.

Skin corrosion/irritation- causes severe skin burns and eye damage.

Serious eye damage/eye irritation- causes serious eye damage.

Respiratory or skin sensitization:

Respiratory sensitization- not a respiratory sensitizer.

Skin sensitization- this product is not expected to cause skin sensitization.

Reproductive toxicity: This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -single exposure: May cause respiratory irritation.

Specific target organ toxicity -repeated exposure: Not classified.

Aspiration hazard: Not an aspiration hazard.

Chronic effects: Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

2-Butoxyethanol- (CAS 111-76-2)-

Acute Toxicity-

Acute oral toxicity- LD50 Oral: 1,414 mg/kg

Species: guinea pig

Remarks: Ingestion may cause weakness, confusion, anxiety, decreased blood pressure, and CNS

depression with collapse and coma.

Acute inhalation toxicity- LC50: ~ 932 ppm

Exposure time: 4 HOURS

Species: guinea pig

Remarks: Exposure to vapor may cause irritation of the eyes, nose, and respiratory tract. May cause nausea. May cause headaches. Extensive and prolonged contact with skin may cause confusion, anxiety, decreased blood pressure, and CNS depression with collapse and coma.

Acute dermal toxicity- LD50: > 2,000 mg/kg

Species: guinea pig

Remarks: Minimal hazard by skin contact with liquid or vapor. This material may be absorbed through the skin. High dermal doses (most likely achieved from exposure to undiluted liquid) may cause weakness, headache and nausea. Extensive and prolonged contact with skin may cause confusion, anxiety, decreased blood pressure, and CNS depression with collapse and coma.

Skin corrosion/irritation- causes moderate skin irritation.

Serious eye damage/eye irritation- causes moderate eye damage.

Respiratory or skin sensitization:

Skin sensitization- this product is not expected to cause skin sensitization.

Reproductive toxicity: OECD Test No. 416: Two-Generation Reproduction Toxicity Study (Mouse, Male and Female); NOAEL: 720 mg/kg; NOAEL: 720 mg/kg; NOAEL: 720 mg/kg; Ingestion

Developmental toxicity: Rat, Male and Female; NOAEL: 100 mg/kg; NOAEL: 30 mg/kg; Ingestion

Specific target organ toxicity -single exposure: Not classified.

Specific target organ toxicity -repeated exposure: Not classified.

Aspiration hazard: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Hydrofluoric Acid- (CAS 7664-39-3)-

Acute toxicity: No data available

Carcinogenicity:

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Hydrofluoric acid)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: No data available

Specific target organ toxicity - single exposure: No data available

Specific target organ toxicity - repeated exposure: No data available

Aspiration hazard: No data available

Additional Information

RTECS: Not available

Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia., Material can cause severe burns and blistering which may not be immediately painful or visible. The full extent of tissue damage may not exhibit itself for 12-24 hours after exposure., Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., necrosis of the skin.

SECTION 12- ECOLOGICAL INFORMATION

Sulfuric Acid 93% (CAS 7664-93-9)-

Ecotoxicity: Harmful to aquatic life with long lasting effects. Because of the low pH of this product, it would be expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Aquatic toxicity- LC50 Oral: 45.0644 mg/l

Duration: 96 hours **Species**: fish

Persistence and degradability: No data is available on the degradability of this product.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

2-Butoxyethanol- (CAS 111-76-2)-

Ecotoxicity:

Aquatic toxicity (fish)-LC-50: 1,474 mg/l

Duration: 96 hours

Species: Oncorhynchus mykiss,

Aquatic toxicity (Aquatic Invertebrates)- EC-50: 1,550 mg/l

Duration: 48 hours **Species:** water flea

Chronic hazards to the aquatic environment:

Toxicity (fish)- NOEC >100 mg/l

Duration: 21 days **Species:** Zebra Fish

Toxicity (Aquatic Invertebrates)- NOEC: 100 mg/l

Duration: 21 days **Species:** daphnid

Toxicity (Aquatic Plants)- EC-50: 1,840 mg/l

Duration: 72 hours

Species: Algae (Pseudokirchneriella subcapitata)

Persistence and degradability: 90.4 % (28 d) Readily biodegradable

Bioaccumulative potential: Potential to bioaccumulate is low.

Partition Coefficient n-octanol / water (log Kow): Log Kow: 0.81 20 °C

Mobility in soil: Expected to partition to water.

Hydrofluoric Acid- (CAS 7664-39-3)-

Ecotoxicity: No data available

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

SECTION 13- DISPOSAL CONSIDERATIONS

Further information: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of as hazardous waste in compliance with local and national regulations.

SECTION 14- TRANSPORT INFORMATION

Transport in accordance with all federal, state and local regulations.

DOT-

UN Number: UN 3264

UN proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s. (Hydrofluoric & Sulfuric Acid)

Hazard class: 8 Packing group: II

SECTION 15- REGULATORY INFORMATION

US federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

CERCLA Hazardous Substance List (40 CFR 302.4):

Sulfuric Acid (CAS 7664-93-9) Listed.

SARA 304 Emergency release notification:

Sulfuric Acid (CAS 7664-93-9) 1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Not listed.

SARA 302 Extremely hazardous substance:

Sulfuric Acid (CAS 7664-93-9) 1000 LBS

Hydrofluoric acid (CAS 7664-93-3)

SARA 311/312 Hazardous Chemical:

Sulfuric Acid (CAS 7664-93-9)

2-Butoxyethanol (CAS 111-76-2)- immediate (acute) health hazard ; delayed (chronic) health hazard ; fire hazard

SARA 313 (TRI reporting):

Sulfuric Acid (CAS 7664-93-9)

Hydrofluoric acid (CAS 7664-93-3)

2-Butoxyethanol (CAS 111-76-2)

Other federal regulations-

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Sulfuric Acid (CAS 7664-93-9)

US state regulations-

US - California Candidate Chemicals: Listed on initial list:

Sulfuric Acid (CAS 7664-93-9)

US. Massachusetts RTK - Substance List:

Sulfuric Acid (CAS 7664-93-9)

Hydrofluoric acid (CAS 7664-93-3)

US. New Jersey Worker and Community Right-to-Know Act:

Sulfuric Acid (CAS 7664-93-9)

Hydrofluoric acid (CAS 7664-93-3)

US. Pennsylvania Worker and Community Right-to-Know Law:

Sulfuric Acid (CAS 7664-93-9)

Hydrofluoric acid (CAS 7664-93-3)

US. Rhode Island RTK

Sulfuric Acid (CAS 7664-93-9)

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance:

Sulfuric Acid (CAS 7664-93-9) Listed: March 14, 2003

SECTION 16- OTHER INFORMATION

NFPA RATING:

Health- 0 Flammability- 3 Reactivity- 0

HMIS RATING:

Health- 3 Flammability- 0 Physical Hazard- 0 Personal Protection- C

References: Not available

Other Special Considerations: Not available

Created: 06/01/2015 Revised From: 05/19/2014

DISCLAIMER:

The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable. Information is correct to the best of our knowledge at the date of the MSDS publication.