



SAFETY DATA SHEET

Panel Bonder 3500 Hardener

Page: 1

Revision: 03/03/2014

1. Product and Company Identification

Product Code: CE-PB (H)
Product Name: Panel Bonder 3500 Hardener
Company Name: Crest Industries, Inc.
1337 King Road
Trenton, MI 48183
Phone Number: (734)479-4141
Web site address: crestauto.com
Emergency Contact: Chemtel (800)255-3924
International Calls (813)248-0585
Stock Number(s): CE-PB

2. Hazards Identification

Skin Corrosion/Irritation, Category 1A-1C

Serious Eye Damage/Eye Irritation, Category 1

Skin Sensitization, Category 1

Toxic To Reproduction, Category 1B



GHS Signal Word: Danger

GHS Hazard Phrases: H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H360 - May damage fertility or the unborn child .

GHS Precaution Phrases: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P281 - Use personal protective equipment as required.

GHS Response Phrases: P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P333+313 - If skin irritation or rash occurs, get medical advice/attention.
P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases: P405 - Store locked up.
P501 - Dispose of contents/container to an approved treatment/storage/disposal facility in accordance with local/regional/national and international regulations.



SAFETY DATA SHEET

Panel Bonder 3500 Hardener

Page: 2

Revision: 03/03/2014

Potential Health Effects (Acute and Chronic):

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation.

Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation.

Eye Contact: Causes eye irritation.

Ingestion: May be harmful if swallowed.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
60676-86-0	Silica, Fused	12.00 - 15.00 %
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	5.000 - 10.00 %
15520-10-2	1,5-Pentanediamine, 2-methyl-	1.500 - 2.000 %
14464-46-1	Cristobalite	0.130 %
NA	Aromatic Amine	1.000 - 2.000 %
71074-89-0	bis[(dimethylamino)methyl]phenol	1.000 - 2.000 %
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	12.00 - 15.00 %

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician.

In Case of Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

5. Fire Fighting Measures

Flash Pt: 93.4 C (200 F)

Explosive Limits: LEL: UEL:

Autoignition Pt: NA

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Flammable Properties and

Hazards:

Hazardous Combustion

Products:



6. Accidental Release Measures

**Steps To Be Taken In Case
Material Is Released Or
Spilled:**

Personal precautions.
Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation.
Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
Discharge into the environment must be avoided.

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

7. Handling and Storage

**Precautions To Be Taken in
Handling:**

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.
Normal measures for preventive fire protection.

**Precautions To Be Taken in
Storing:**

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
60676-86-0	Silica, Fused	PEL: 80 mg/m3/(%SiO ₂)	TLV: 0.1 mg/m3 (R)	
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol			
15520-10-2	1,5-Pentanediamine, 2-methyl-			
14464-46-1	Cristobalite	PEL: 4412 ppm/(%SiO ₂ +5)	TLV: 0.05 mg/m3 (R)	
NA	Aromatic Amine			
71074-89-0	bis[(dimethylamino)methyl]phenol			
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamin e)			

**Respiratory Equipment
(Specify Type):**

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Eye Protection:

Face shield and safety glasses.

Protective Gloves:

Handle with gloves. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

**Engineering Controls
(Ventilation etc.):**

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

**Work/Hygienic/Maintenance
Practices:**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.



9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Tan.
Faint. amine-like.

pH:

Melting Point: NA - 0 C (32.0 F)

Boiling Point: ~ 302 C (576 F)

Flash Pt: 93.4 C (200 F)

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or mm Hg):

Vapor Density (vs. Air = 1):

Specific Gravity (Water = 1):

Density: 1.13 G/CM3

Solubility in Water:

Octanol/Water Partition

Coefficient:

Autoignition Pt: NA

Decomposition Temperature: NA

Viscosity:

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - No data available.

Instability:

Incompatibility - Materials To Strong oxidizing agents, acids, Amines, Bases.

Avoid:

Hazardous Decomposition or formed under fire conditions. Nature of decomposition products unknown.

Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -

Hazardous Reactions:



11. Toxicological Information

Toxicological Information:

Irritation or Corrosion: No data available.

Carcinogenicity/Other Carcinogenicity.

Information: IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
60676-86-0	Silica, Fused	n.a.	n.a.	n.a.	n.a.
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	n.a.	n.a.	n.a.	n.a.
15520-10-2	1,5-Pentanediamine, 2-methyl-	n.a.	n.a.	n.a.	n.a.
14464-46-1	Cristobalite	Known	2A	A2	n.a.
NA	Aromatic Amine	n.a.	n.a.	n.a.	n.a.
71074-89-0	bis[(dimethylamino)methyl]phenol	n.a.	n.a.	n.a.	n.a.
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information:

Toxicity: no data available.
PBT and vPvB assessment: no data available.
Other adverse effects.
An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Persistence and Degradability:

Toxic to aquatic life with long lasting effects. No data available.
Biodegradability: Result: 2 % -According to the results of tests of biodegradability this product is not readily biodegradable.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available.

13. Disposal Considerations

Waste Disposal Method:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging.
Dispose of as unused product.

14. Transport Information



SAFETY DATA SHEET

Panel Bonder 3500 Hardener

Page: 6

Revision: 03/03/2014

LAND TRANSPORT (US DOT):**DOT Proper Shipping Name:** Limited Quantity.**DOT Hazard Class:****UN/NA Number:** None**LAND TRANSPORT (Canadian TDG):****TDG Shipping Name:****UN Number:** None**Hazard Class:****TDG Classification:****MARINE TRANSPORT (IMDG/IMO):****IMDG/IMO Shipping Name:** Corrosive liquid, basic, organic, n.o.s.**UN Number:** 3267**Packing Group:** III**Hazard Class:****IMDG MFAG Number:****IMDG EMS Page:****AIR TRANSPORT (ICAO/IATA):****ICAO/IATA Shipping Name:** Corrosive liquid, basic, organic, n.o.s.**UN Number:** 3267**Packing Group:** III**Hazard Class:**

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
60676-86-0	Silica, Fused	No	No	No
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	No	No	No
15520-10-2	1,5-Pentanediamine, 2-methyl-	No	No	No
14464-46-1	Cristobalite	No	No	No
NA	Aromatic Amine	No	No	No
71074-89-0	bis[(dimethylamino)methyl]phenol	No	No	No
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No

This material meets the EPA ☒ Yes ☐ No **Acute (immediate) Health Hazard**
'Hazard Categories' defined ☒ Yes ☐ No **Chronic (delayed) Health Hazard**
for SARA Title III Sections ☐ Yes ☒ No **Fire Hazard**
311/312 as indicated: ☐ Yes ☒ No **Sudden Release of Pressure Hazard**
☐ Yes ☒ No **Reactive Hazard**

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
60676-86-0	Silica, Fused	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1656; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
15520-10-2	1,5-Pentanediamine, 2-methyl-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
14464-46-1	Cristobalite	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA



SAFETY DATA SHEET

Panel Bonder 3500 Hardener

Page: 7

Revision: 03/03/2014

NA	Aromatic Amine	Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1657; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
71074-89-0	bis[(dimethylamino)methyl]phenol	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

16. Other Information

Revision Date: 03/03/2014

**Additional Information About
This Product:**

**Company Policy or
Disclaimer:**

The information contained in this SDS is believed to be accurate and reliable as of the date indicated. Crest Industries, Inc. assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.



SAFETY DATA SHEET

Panel Bonder 3500 Resin

Page: 1

Revision: 03/03/2014

1. Product and Company Identification

Product Code: CE-PB (R)
Product Name: Panel Bonder 3500 Resin
Company Name: Crest Industries, Inc.
1337 King Road
Trenton, MI 48183
Phone Number: (734)479-4141
Web site address: crestauto.com
Emergency Contact: Chemtel (800)255-3924
International Calls (813)248-0585
Stock Number(s): CE-PB

2. Hazards Identification

Skin Sensitization, Category 1B

Serious Eye Damage/Eye Irritation, Category 1

Carcinogenicity, Category 2



GHS Signal Word: Danger

GHS Hazard Phrases: H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H351 - Suspected of causing cancer .

GHS Precaution Phrases: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P333+313 - If skin irritation or rash occurs, get medical advice/attention.
P362+364 - Take off contaminated clothing and wash it before reuse.

GHS Storage and Disposal Phrases: P405 - Store locked up.
P501 - Dispose of contents/container to an approved treatment/storage/disposal facility in accordance with local/regional/national and international regulations.

**Potential Health Effects
(Acute and Chronic):**

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation.
Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation.
Eye Contact: Causes eye irritation.
Ingestion: May be harmful if swallowed.



3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
60676-86-0	Silica, Fused	15.00 - 20.00 %
14464-46-1	Cristobalite	0.140 %
NA	Polymer	50.00 - 60.00 %
1333-86-4	Carbon black	0.100 - 0.500 %
NA	Epoxy Resin Modifier	10.00 - 15.00 %
NA	Organosiloxane	1.500 - 5.000 %

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician.

In Case of Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

5. Fire Fighting Measures

Flash Pt: 99.0 C (210 F)

Explosive Limits: LEL: UEL:

Autoignition Pt: NA

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Environmental precautions. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Keep in suitable, closed containers for disposal.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Normal measures for preventive fire protection.

Precautions To Be Taken in Storing: Keep container tightly closed in a dry and well-ventilated place.



SAFETY DATA SHEET

Panel Bonder 3500 Resin

Page: 3

Revision: 03/03/2014

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
60676-86-0	Silica, Fused	PEL: 80 mg/m3/(%SiO2)	TLV: 0.1 mg/m3 (R)	
14464-46-1	Cristobalite	PEL: 4412 ppm/(%SiO2+5)	TLV: 0.05 mg/m3 (R)	
NA	Polymer			
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3.5 mg/m3	
NA	Epoxy Resin Modifier			
NA	Organosiloxane			

Respiratory Equipment (Specify Type): Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Eye Protection: Face shield and safety glasses.

Protective Gloves: Handle with gloves. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Use with adequate ventilation.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Black.
Faint.

pH:

Melting Point: NA - 5.00 C (41.0 F)

Boiling Point: NA

Flash Pt: 99.0 C (210 F)

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or mm Hg):

Vapor Density (vs. Air = 1):

Specific Gravity (Water = 1):

Density: 1.089 G/CM3

Solubility in Water:

Octanol/Water Partition Coefficient:

Autoignition Pt: NA

Decomposition Temperature:

Viscosity:



10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Excess heat.

Instability:

Incompatibility - Materials To Avoid: Strong oxidizing agents, acids.

Hazardous Decomposition or Byproducts: Hazardous decomposition products formed under fire conditions.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions:

11. Toxicological Information

Toxicological Information:

Irritation or Corrosion: No data available.

Carcinogenicity/Other Information: Carcinogenicity.
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
60676-86-0	Silica, Fused	n.a.	n.a.	n.a.	n.a.
14464-46-1	Cristobalite	Known	2A	A2	n.a.
NA	Polymer	n.a.	n.a.	n.a.	n.a.
1333-86-4	Carbon black	n.a.	2B	A4	n.a.
NA	Epoxy Resin Modifier	n.a.	n.a.	n.a.	n.a.
NA	Organosiloxane	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information: Toxicity: no data available.
PBT and vPvB assessment: no data available.
Other adverse effects.
An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Persistence and Degradability: Toxic to aquatic life with long lasting effects. No data available.
Biodegradability: Result: 2 % -According to the results of tests of biodegradability this product is not readily biodegradable.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.



SAFETY DATA SHEET

Panel Bonder 3500 Resin

Page: 5

Revision: 03/03/2014

13. Disposal Considerations

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging.
Dispose of as unused product.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Limited Quantity.

DOT Hazard Class:

UN/NA Number: None

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:

UN Number: None

Hazard Class:

TDG Classification:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Corrosive liquid, basic, organic, n.o.s.

UN Number: 3267

Hazard Class:

Packing Group: III

IMDG MFAG Number:

IMDG EMS Page:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Corrosive liquid, basic, organic, n.o.s.

UN Number: 3267

Hazard Class:

Packing Group: III

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
60676-86-0	Silica, Fused	No	No	No
14464-46-1	Cristobalite	No	No	No
NA	Polymer	No	No	No
1333-86-4	Carbon black	No	No	No
NA	Epoxy Resin Modifier	No	No	No
NA	Organosiloxane	No	No	No

This material meets the EPA ☒ Yes ☐ No **Acute (immediate) Health Hazard**
'Hazard Categories' defined ☒ Yes ☐ No **Chronic (delayed) Health Hazard**
for SARA Title III Sections ☐ Yes ☒ No **Fire Hazard**
311/312 as indicated: ☐ Yes ☒ No **Sudden Release of Pressure Hazard**
☐ Yes ☒ No **Reactive Hazard**

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
60676-86-0	Silica, Fused	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1656; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
14464-46-1	Cristobalite	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -



SAFETY DATA SHEET

Panel Bonder 3500 Resin

Page: 6

Revision: 03/03/2014

NA Polymer

1333-86-4 Carbon black

NA Epoxy Resin Modifier

NA Organosiloxane

Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1657; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No

CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 0342; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes

CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

16. Other Information

Revision Date: 03/03/2014

Additional Information About

This Product:

Company Policy or

Disclaimer:

The information contained in this SDS is believed to be accurate and reliable as of the date indicated. Crest Industries, Inc. assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.