

## 1. IDENTIFICATION

**Product identifier**
**Product Name** EVERCOAT RAGE GOLD EXP

**Other means of identification**
**Product Code** 101112

**Recommended use of the chemical and restrictions on use**
**Recommended Use** Premium Light Weight Body Filler. For professional use only.

**Uses advised against** Uses other than recommended use.

**Details of the supplier of the safety data sheet**
**Manufacturer Address**

ITW Evercoat  
A division of Illinois Tool Works Inc.  
6600 Cornell Road  
Cincinnati, OH 45242 USA  
513-489-7600

**May Also Be Distributed by:**

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**24-hour emergency phone number**

CHEMTREC: 1-800-424-9300  
INTERNATIONAL: 1-703-527-3887

**E-mail address:** Info@evercoat.com

## 2. HAZARDS IDENTIFICATION

**Classification**
**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

**Label elements**
**Emergency Overview**
**Signal word**
**Danger**

Harmful if swallowed or if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause cancer  
Suspected of damaging fertility or the unborn child

Causes damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor



**Appearance** Gray

**Physical state** Liquid

**Odor** Pungent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
In case of inadequate ventilation wear respiratory protection  
Contaminated work clothing should not be allowed out of the workplace  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use non-sparking tools  
Take precautionary measures against static discharge  
Wear protective gloves/protective clothing/eye protection/face protection

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
If skin irritation or rash occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician  
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
Rinse mouth  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

#### Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep cool

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

May be harmful in contact with skin. Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Talc (hydrous magnesium silicate)	14807-96-6	10 - 30
Styrene	100-42-5	10 - 30
Ground Limestone (Calcium Carbonate)	1317-65-3	7 - 13
Magnesite	546-93-0	5 - 10
Trade Secret	Proprietary	1 - 5
Zinc Phosphate	7779-90-0	0.1 - 1
Benzenamine, N,N,4-Trimethyl	99-97-8	0.1 - 1

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	Get medical advice/attention if you feel unwell.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Ingestion</b>	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

#### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	See section 2 for more information.
-----------------	-------------------------------------

#### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Dry chemical, Foam

#### Unsuitable extinguishing media

None

#### Specific hazards arising from the chemical

Flammable.

#### Explosion data

<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Use personal protective equipment as required.

### Environmental precautions

**Environmental precautions** See section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Soak up with inert absorbent material.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc (hydrous magnesium silicate) 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Styrene 100-42-5	STEL: 40 ppm TWA: 20 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m <sup>3</sup> (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m <sup>3</sup> Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m <sup>3</sup> STEL: 100 ppm STEL: 425 mg/m <sup>3</sup>
Ground Limestone (Calcium Carbonate) 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Magnesite 546-93-0	-	-	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Minimize exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

**Physical state** Liquid

**Appearance** Gray

**Odor** Pungent

**Odor threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	145 °C / 293 °F	
Flash point	38 °C / 100 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

**Other Information**

**Softening point** No information available

**Molecular weight** No information available

**VOC Content (%)** No information available

**Applied** 0.28 lbs/gal

**Packaged** 1.35 lbs/gal

**Density** No information available

**Bulk density** 8.75

**SADT (self-accelerating decomposition temperature)** No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**

No information available

**Chemical stability**

Stable under normal conditions

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Excessive heat.

**Incompatible materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Carbon oxides

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

<b>Inhalation</b>	May cause irritation of respiratory tract.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	= 11.7 mg/L ( Rat ) 4 h
Trade Secret	= 5410 mg/kg ( Rat )	-	-
Zinc Phosphate 7779-90-0	> 5000 mg/kg ( Rat )	-	-
Benzenamine, N,N,4-Trimethyl 99-97-8	= 1650 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 1400 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc (hydrous magnesium silicate) 14807-96-6	-	Group 3	-	X
Styrene 100-42-5	-	Group 2A	Reasonably Anticipated	X
Benzenamine, N,N,4-Trimethyl 99-97-8	-	Group 2B	-	X

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

Group 2A - Probably Carcinogenic to Humans

NTP (National Toxicology Program)

*Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen*

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Chronic toxicity**

May cause adverse liver effects. Contains a known or suspected reproductive toxin.

**Target Organ Effects**

Central nervous system, Central Vascular System (CVS), Eyes, Liver, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1095 mg/kg

ATEmix (dermal) 2273 mg/kg

ATEmix (inhalation-dust/mist) 1.8 mg/l

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity****Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical Name	Partition coefficient
Styrene 100-42-5	2.95
Benzenamine, N,N,4-Trimethyl 99-97-8	2.81

**Other adverse effects**

No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Disposal of wastes**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging**

Do not reuse container.

**US EPA Waste Number**

D001, U166 U197

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Styrene 100-42-5	Toxic Ignitable
Zinc Phosphate 7779-90-0	Toxic

## 14. TRANSPORT INFORMATION

Note:

This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all

applicable laws, regulations and rules relating to the transportation of the material.

**DOT**

UN/ID No UN3269  
 Proper shipping name: Polyester Resin Kit  
 Hazard Class 3  
 Packing Group III

**IATA**

UN/ID No UN3269  
 Proper shipping name: Polyester Resin Kit  
 Hazard Class 3  
 Packing Group III

**IMDG**

UN/ID No UN3269  
 Proper shipping name: Polyester Resin Kit  
 Hazard Class 3  
 Packing Group III

## 15. REGULATORY INFORMATION

**International Inventories**

TSCA Complies  
 DSL/NDL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1

**SARA 311/312 Hazard Categories**

Acute health hazard No  
 Chronic Health Hazard No  
 Fire hazard Yes  
 Sudden release of pressure hazard No  
 Reactive Hazard No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene	1000 lb	-	-	X



100-42-5				
Zinc Phosphate 7779-90-0	-	X	-	-

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Styrene 100-42-5	Carcinogen
Benzenamine, N,N,4-Trimethyl 99-97-8	Carcinogen
Crystalline Silica (Quartz) 14808-60-7	Carcinogen
Titanium Dioxide 13463-67-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Talc (hydrous magnesium silicate) 14807-96-6	X	X	X
Styrene 100-42-5	X	X	X
Ground Limestone (Calcium Carbonate) 1317-65-3	X	X	X
Magnesite 546-93-0	X	X	-
Trade Secret	X	-	-
Trade Secret	X	X	X
1,4-NAPHTHOQUINONE 130-15-4	X	X	X
Trade Secret	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**WHMIS Hazard Class**

B3 - Combustible liquid, D2A - Very toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 2	<b>Instability</b> 0	-
<b>HMIS</b>	<b>Health hazards</b> 2	<b>Flammability</b> 2	<b>Physical hazards</b> 0	<b>Personal protection</b> B

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

**Revision Date** 19-Nov-2019

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this

product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**