valspar if it matters, we're on it.®

SAFETY DATA SHEET

Revision date 25-Jan-2020

Version 6

Supersedes Date: 14-Jan-2020

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier Product Code MA-232

Product Name DTM ACTIVATOR

Other means of identification No information available

Recommended use of the chemical and restrictions on use Hardener, Coatings

Details of the supplier of the safety data sheet See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address

msds@valspar.com

Emergency telephone number United States of America 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Highly flammable liquid and vapor Causes skin irritation Causes serious eye irritation Suspected of causing cancer May cause respiratory irritation May be fatal if swallowed and enters airways May cause damage to the following organs through prolonged or repeated exposure: Ears

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

OTHER HAZARDS

Not applicable.

UNKNOWN ACUTE TOXICITY

0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	25 - 50
Xylenes	1330-20-7	10 - 25
Ethylbenzene	100-41-4	1 - 3
1-Butanol	71-36-3	1 - 3
2-Pentanone, 4-methyl-	108-10-1	1 - 3

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms

No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons:

Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Incompatible materials

Strong oxidizing agents.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m³ F	
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
1-Butanol	TWA: 20 ppm	TWA: 100 ppm	IDLH: 1400 ppm

71-36-3		TWA: 300 mg/m ³	Ceiling: 50 ppm
			Ceiling: 150 mg/m ³
2-Pentanone, 4-methyl-	STEL: 75 ppm	TWA: 100 ppm	IDLH: 500 ppm
108-10-1	TWA: 20 ppm	TWA: 410 mg/m ³	TWA: 50 ppm
			TWA: 205 mg/m ³
			STEL: 75 ppm
			STEL: 300 mg/m ³

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Odor Color Odor Threshold	liquid No information available Solvent colorless No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range flash point	114 °C / 237 °F 7 °C / 45 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (Ibs per US gallon)	9.12
specific gravity	1.09
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Other information

	Section 10: STABILITY AND REACTIVITY
Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Chlorine.

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Causes serious eye irritation Skin Contact Causes skin irritation Ingestion May be fatal if swallowed and enters airways Inhalation May cause respiratory irritation

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	= 13 g/kg (Rat)	>2 mL/kg (Rabbit)	= 33 mg/L (Rat)4 h
Xylenes 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit)> 4350 mg/kg (Rabbit)	= 5000 ppm (Rat)4 h = 29.08 mg/L (Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
1-Butanol 71-36-3	= 700 mg/kg (Rat)= 790 mg/kg (Rat)	= 3402 mg/kg (Rabbit)= 3400 mg/kg (Rabbit)	> 8000 ppm (Rat)4 h
2-Pentanone, 4-methyl- 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg(Rabbit)	= 8.2 mg/L (Rat)4 h

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	20254 Mg/kg
ATEmix (dermal)	9195 Mg/kg
ATEmix (inhalation-dust/mist)	9.1 mg/l
ATEmix (inhalation-vapor)	67 mg/l

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100-41-4	A3	Group 2B		Х
2-Pentanone, 4-methyl-	A3	Group 2B		Х

108-10-1					
ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen. IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans. OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present.					
Skin corrosion/irritation Causes skin irritation Serious eye damage/eye irritation Causes serious eye irritation Skin sensitization Not applicable Respiratory sensitization Not applicable Germ cell mutagenicity Not applicable Carcinogenicity Suspected of causing cancer Reproductive Toxicity Not applicable Specific target organ toxicity (single exposure) May cause respiratory irritation Specific target organ toxicity (repeated exposure) May cause damage to the following organs through prolonged or repeated exposure: Ears Aspiration hazard May be fatal if swallowed and enters airways					
	Section 12: ECOLO	GICAL INFORMAT	ION		
Ecotoxicity Environmental precautions	Prevent product from enter	ering drains.			
Persistence and degradal No information available	bility				
Bioaccumulation No information available					
<u>Mobility</u> No information available					
Other adverse effects	No information available				
Section 13: DISPOSAL CONSIDERATIONS					
Waste treatment methods					
Disposal of wastes	Disposal should be in acc regulations.	cordance with applicable	e regional, national and local laws and		
Contaminated packaging	Improper disposal or reus containers must be scrap		be dangerous and illegal. Empty		
Section 14: TRANSPORT INFORMATION					
14.1 UN/ID no 14.2 Proper shipping name	DOT UN1263 Paint related material	IMDG UN1263 Paint related material	IATA UN1263 Paint related material		
14.3 Hazard Class 14.4 Packing Group 14.5 Environmental hazard 14.6 Special Provisions	3 II 149, B52, IB2, T4, TP1, TP8, TP28, 367 Emergency Response Guide Number	3 II 163, 367 EmS-No F-E, S-E	3 II A3, A72, A192		
14.7 Transport in bulk accor	128 ding to Annex II of MARPOL 73/78 and	the IBC Code	No information available		

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c),

ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing. (Active List). All components are listed or exempt from listing

US Federal Regulations

Chemical Name	TSCA - Toxic Substances Control Act, Section 12(b) Export Notification
Benzene, 1-chloro-4-(trifluoromethyl)-	Section 4
98-56-6	

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Xylenes 1330-20-7 10 - 25	1		Present
Ethylbenzene 100-41-4 1 - 3	0.1		Present
1-Butanol 71-36-3 1 - 3	1		
2-Pentanone, 4-methyl- 108-10-1 1 - 3	1		Present

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylenes 1330-20-7	100 lb			Х
Ethylbenzene 100-41-4	1000 lb	Х	X	Х

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylenes	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ
1-Butanol	5000 lb		RQ 5000 lb final RQ
71-36-3			RQ 2270 kg final RQ
2-Pentanone, 4-methyl-	5000 lb		RQ 5000 lb final RQ
108-10-1			RQ 2270 kg final RQ

US State Regulations

Rule 66 status of product

Photochemically reactive.

California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

Chemical Name

Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6		
Proprietary Non-Hazardous Ingredient - Proprietary CAS		
Xylenes		
1330-20-7		
Ethylbenzene		
100-41-4		
1-Butanol		
71-36-3		
2-Pentanone, 4-methyl-		
108-10-1		

3*

Section 16: OTHER INFORMATION

HMIS	
Health	hazards
*	Chronic H

* = Chronic Health Hazard	
Flammability	3
Physical hazards	0
Personal Protection	Х

Supplier Address

Valspar Coatings	Valspar Automotive
701 Shiloh Rd.	600 Nova Drive S.E.
Garland, TX 75042	Massillon, OH 44646
972-276-5181	330-830-6000

Prepared By

Product Stewardship

Revision date Revision Note 25-Jan-2020 No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet