

SECTION 1: Identification

1.1. Identification

Product name : ProTouch BaseCoat

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Automotive Refinish

1.3. Details of the supplier of the safety data sheet

Supplies Plus, INC
3453 Fowler Street
Ft. Myers, FL 33901

1.4. Emergency telephone number

Emergency number : 239 - 334 - 6676

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | |
|---------------------------|------|
| Flam. Liq. 2 | H225 |
| Acute Tox. 4 (Oral) | H302 |
| Acute Tox. 3 (Inhalation) | H331 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2A | H319 |
| Skin Sens. 1 | H317 |
| Carc. 2 | H351 |
| Repr. 2 | H361 |
| STOT SE 3 | H336 |
| STOT RE 1 | H372 |
| Aquatic Acute 3 | H402 |
| Aquatic Chronic 3 | H412 |

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H361 - Suspected of damaging fertility or the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe dust/fume/gas/mist/vapors/spray

ProTouch

Safety Data Sheet

P264 - Wash thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing must not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a poison center/doctor if you feel unwell
P330 - Rinse mouth
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use water fog, alcohol resistant foam, carbon dioxide and dry chemical powder to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

ct

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|-------------------------------------------|---------------------|-----------|-------------------------------------------------------------------------------------------------------------|
| n-Butyl acetate | (CAS No) 123-86-4 | 10 - 20 | Flam. Liq. 2, H225 |
| Methyl Acetate | (CAS No) 79-20-9 | 20 - 30 | Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 |
| n-Butyl Alcohol | (CAS No) 71-36-3 | 0.5 - 1.5 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 |
| Propylene glycol monomethyl ether acetate | (CAS No) 108-65-6 | 1 - 5 | Flam. Liq. 3, H226 |
| Ethylbenzene | (CAS No) 100-41-4 | 1 - 5 | Flam. Liq. 2, H225 Carc. 2, H351 |
| Liquid HALS | (CAS No) 41556-26-7 | 0.1 - 1.0 | Flam. Liq. 2 H226 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen or artificial respiration if needed. Seek medical attention.
- First-aid measures after skin contact : Remove contaminated clothing immediately and wash skin with soap and water. Seek medical attention if irritation develops or persists. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

ProTouch

Safety Data Sheet

First-aid measures after ingestion : Rinse mouth. If vomiting occurs, keep head low so that stomach contents don't get into lungs. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Toxic if inhaled. May cause drowsiness, dizziness, headache and nausea.
Symptoms/injuries after skin contact : Causes skin irritation. May cause redness, pain and an allergic skin reaction.
Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms include stinging, tearing, redness, swelling and blurred vision.
Symptoms/injuries after ingestion : Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use water fog, alcohol resistant foam, carbon dioxide and dry chemical powder to extinguish.
Unsuitable extinguishing media : Do not use water jet as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.
Explosion hazard : Vapors may form explosive mixtures with air.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Keep unnecessary personnel away from and upwind of spill.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk.
Methods for cleaning up : Eliminate all ignition sources. Keep combustible away from spilled material. Take precautionary measures against static discharge. Confine spill and soak up with non-combustible absorbent (vermiculite, sand or earth). Place in an approved container and dispose in accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Do not breathe mist or vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from open flames, hot surfaces and sources of ignition. Prevent electrostatic charge build up by using common bonding and grounding techniques. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| n-Butyl acetate (123-86-4) | | |
|----------------------------|-------------------------------------|-----------------------|
| ACGIH | ACGIH TWA (ppm) | 50 ppm |
| ACGIH | ACGIH STEL (ppm) | 150 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 710 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 150 ppm |

ProTouch

Safety Data Sheet

| n-Butyl acetate (123-86-4) | | |
|-------------------------------------------------------------|---------------------------------------|-----------------------|
| IDLH | US IDLH (ppm) | 1700 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 710 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 150 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 950 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 200 ppm |
| Methyl Acetate (79-20-9) | | |
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 610 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 250 ppm |
| IDLH | US IDLH (ppm) | 3100 ppm |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 610 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 250 ppm |
| Propylene glycol monomethyl ether acetate (108-65-6) | | |
| AIHA | WEEL TWA (ppm) | 50 ppm |
| Ethylbenzene (100-41-4) | | |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| IDLH | US IDLH (ppm) | 800 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 435 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 545 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 125 ppm |
| n-Butyl Alcohol (71-36-3) | | |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| NIOSH | NIOSH REL (TWA) (ppm) | 50 ppm |
| IDLH | US IDLH (ppm) | 1400 ppm |

8.2. Exposure controls

| | |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Appropriate engineering controls | : Explosion proof local exhaust and general ventilation must be adequate to meet exposure standards. |
| Hand protection | : Use chemical resistant gloves. |
| Eye protection | : Safety glasses with side shields or goggles (when splashing is likely). |
| Skin and body protection | : Wear suitable working clothes. |
| Respiratory protection | : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|----------------|-----------|
| Physical state | : Liquid |
| Color | : Blue |
| Odor | : Solvent |

ProTouch

Safety Data Sheet

| | |
|---------------------------------------------|-----------------------|
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : -20.0 °C (-4.0 °F) |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Density | : 9.70 lbs/gal |
| Specific gravity | : 0.99 |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : 419.00 °C (786.2°F) |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : 360 cPs |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

VOC Content : 3.1 lb/gal (375.1 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong acids, oxidizing agents, nitrates, halogens.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: Toxic if inhaled.

| n-Butyl acetate (123-86-4) | |
|-----------------------------------|---------------|
| LD50 oral rat | 10768 mg/kg |
| LD50 dermal rabbit | > 17600 mg/kg |
| LC50 inhalation rat (ppm) | 390 ppm/4h |
| ATE US (oral) | 10768 mg/kg |

| Methyl n-amyl ketone (110-43-0) | |
|----------------------------------------|--------------------------------------|
| LD50 oral rat | 1600 mg/kg |
| LD50 dermal rabbit | 12.6 ml/kg |
| LC50 inhalation rat (ppm) | 2000 - 4000 ppm (Exposure time: 6 h) |
| ATE US (oral) | 1670 mg/kg |

ProTouch

Safety Data Sheet

| | |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | > 4350 mg/kg |
| LC50 inhalation rat (mg/l) | 29.08 mg/l/4h |
| ATE US (oral) | 4300 mg/kg |
| ATE US (dermal) | 1100 mg/kg |
| Propylene glycol monomethyl ether acetate (108-65-6) | |
| LD50 oral rat | 8532 mg/kg |
| LD50 dermal rabbit | > 5 g/kg |
| ATE US (oral) | 8532 mg/kg |
| Ethylbenzene (100-41-4) | |
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | 15400 mg/kg |
| LC50 inhalation rat (mg/l) | 17.4 mg/l/4h |
| ATE US (oral) | 3500 mg/kg |
| ATE US (dermal) | 15354 mg/kg |
| Dibutyltin dilaurate (77-58-7) | |
| LD50 oral rat | 45 mg/kg |
| LD50 dermal rabbit | 630 mg/kg |
| ATE US (oral) | 175 mg/kg |
| Toluene (108-88-3) | |
| LD50 oral rat | >2000 mg/kg (5580 mg/kg bodyweight;Rat;Rat;Experimental Value) |
| LD50 dermal rabbit | >12223 mg/kg(>5000 mg/kg bodyweight;Rabbit;Rabbit;Experimental Value) |
| LD50 inhalation rat (mg/l) | >20 mg/l/4h (Rat) |
| Acetone (67-64-1) | |
| LD50 oral rat | 5800 mg/kg(Rat;Equivalent or similar to OECD 401; Experimental Value) |
| LD50 dermal rabbit | 20000 mg/kg(Rabbit;Experimental value;Equivalent or similar to OCED 402;>7426 mg/kg |
| LD50 inhalation rat (mg/l) | 71 mg/l/4h (Rat;Experimental value;76 mg/l/4h;Rat;Experimental value) |
| ATE US (oral) | 5800 mg/kg body weight |
| ATE US (vapors) | 71.000 mg/l/4h |
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not Classified |
| Respiratory or skin sensitization | : Not Classified |
| Germ cell mutagenicity | : Not Classified |
| Carcinogenicity | : Not Classified |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| IARC group | 3 - Not classifiable |
| Ethylbenzene (100-41-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 1 - Evidence of Carcinogenicity |
| In OSHA Hazard Communication Carcinogen list | Yes |
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity – single exposure | : May cause drowsiness or dizziness. |
| Specific target organ toxicity – repeated exposure | : Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |
| SECTION 12: Ecological information | |
| 12.1. Toxicity | |
| n-Butyl acetate (123-86-4) | |
| LC50 fish 1 | 100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| LC50 fish 2 | 17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| Methyl n-amyl ketone (110-43-0) | |
| LC50 fish 1 | 126 - 137 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| LC50 fish 1 | 13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |

ProTouch

Safety Data Sheet

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|-------------------------------------------------------------|----------------------------------------------------------------------------------|
| EC50 Daphnia 1 | 3.82 mg/l (Exposure time: 48 h - Species: water flea) |
| LC50 fish 2 | 2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 Daphnia 2 | 0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris) |
| Propylene glycol monomethyl ether acetate (108-65-6) | |
| LC50 fish 1 | 161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 1 | > 500 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Ethylbenzene (100-41-4) | |
| LC50 fish 1 | 11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 Daphnia 1 | 1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 fish 2 | 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |
| Toluene (108-88-3) | |
| LC50 fish 1 | 24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 84 mg/l (24 h; Daphnia magna; Locomotor effect) |
| Acetone (67-64-1) | |
| LC50 fish 1 | 5540 mg/l (LC50;EU Method C.1;96 h;Salmo gairdneri;Static system;Fresh Water) |
| EC50 Daphnia 1 | 12600 mg/l (LC50;Other' 48h; Daphnia magna;Static system; Fresh Water) |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

| n-Butyl acetate (123-86-4) | |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Log Pow | 1.81 (at 23 °C) |
| Methyl n-amyl ketone (110-43-0) | |
| Log Pow | 1.98 |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| BCF fish 1 | 0.6 - 15 |
| Log Pow | 2.77 - 3.15 |
| Propylene glycol monomethyl ether acetate (108-65-6) | |
| Log Pow | 0.43 |
| Ethylbenzene (100-41-4) | |
| BCF fish 1 | 15 |
| Log Pow | 3.2 |
| Toluene (108-88-3) | |
| BCF Fish | 13.2 (Anguilla japonica) |
| Log Pow | 2.73 (Experimental value;Other;20°C,Experimental value;Other;20 C,Experimental value. |

12.4. Mobility in soil

No additional information available

13.1. Waste treatment methods

12.5. Other adverse effects

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.
Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint related material, 3, II
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint related material
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger

ProTouch

Safety Data Sheet

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
 DOT Packaging Bulk (49 CFR 173.xxx) : 242
 DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
 B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
 T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
 TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
 TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
 TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
 DOT Packaging Exceptions (49 CFR 173.xxx) : 150
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
 DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
 Emergency Response Guide (ERG) Number : 128
 Other information : No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|--------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| n-Butyl acetate (123-86-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| CERCLA RQ | 5000 lb listed under Butyl acetate |
| Methyl n-amyl ketone (110-43-0) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 100 lb |
| SARA Section 313 - Emission Reporting | 1 % |
| Propylene glycol monomethyl ether acetate (108-65-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| EPA TSCA Regulatory Flag | P - P - indicates a commenced PMN substance. |
| Ethylbenzene (100-41-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 1000 lb |
| SARA Section 313 - Emission Reporting | 0.1 % |

ProTouch

Safety Data Sheet

| | |
|---------------------------------------------------------------------------|-------------------------------------------------|
| Dibutyltin dilaurate (77-58-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Toluene (108-88-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Listed on SARA Section 313 (Specific toxic chemical listings) | |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) | 1000 lb |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard / Fire hazard |
| Acetone (67-64-1) | |
| Listed on Unites States TSCA (Toxic Substances Control Act) Inventory | |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) | 5000 lb |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard / Fire hazard |

15.2. US State regulations

| | | | | |
|-------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| Ethylbenzene (100-41-4) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | 54 µg/day |

| | | | | |
|------------------------------------------------------------|--|--|--|--|
| n-Butyl acetate (123-86-4) | | | | |
| U.S. - Massachusetts - Right To Know List | | | | |
| U.S. - Minnesota - Hazardous Substance List | | | | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |
| U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

| | | | | |
|------------------------------------------------------------|--|--|--|--|
| Methyl n-amyl ketone (110-43-0) | | | | |
| U.S. - Massachusetts - Right To Know List | | | | |
| U.S. - Minnesota - Hazardous Substance List | | | | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |
| U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

| | | | | |
|------------------------------------------------------------|--|--|--|--|
| Xylenes (o-, m-, p- isomers) (1330-20-7) | | | | |
| U.S. - Massachusetts - Right To Know List | | | | |
| U.S. - Minnesota - Hazardous Substance List | | | | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |
| U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

| | | | | |
|------------------------------------------------------------|--|--|--|--|
| Ethylbenzene (100-41-4) | | | | |
| U.S. - Massachusetts - Right To Know List | | | | |
| U.S. - Minnesota - Hazardous Substance List | | | | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |
| U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

SECTION 16: Other information

Full text of H-phrases:

| | |
|---------------------------|------------------------------------------------------------------|
| Acute Tox. 3 (Inhalation) | Acute toxicity (inhalation) Category 3 |
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal) Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhalation) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Acute 3 | Hazardous to the aquatic environment - Acute Hazard Category 3 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Carc. 2 | Carcinogenicity Category 2 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Muta. 2 | Germ cell mutagenicity Category 2 |
| Repr. 1B | Reproductive toxicity Category 1B |
| Repr. 2 | Reproductive toxicity Category 2 |
| Skin Corr. 1C | Skin corrosion/irritation Category 1C |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| Skin Sens. 1 | Skin sensitization Category 1 |
| STOT RE 1 | Specific target organ toxicity (repeated exposure) Category 1 |
| STOT SE 1 | Specific target organ toxicity (single exposure) Category 1 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H225 | Highly flammable liquid and vapor |

ProTouch

Safety Data Sheet

| | |
|------|----------------------------------------------------------------|
| H302 | Harmful if swallowed |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H331 | Toxic if inhaled |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H341 | Suspected of causing genetic defects |
| H351 | Suspected of causing cancer |
| H360 | May damage fertility or the unborn child |
| H361 | Suspected of damaging fertility or the unborn child |
| H370 | Causes damage to organs |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product