SECTION	Ι-	IDEN	TIFICATION
---------	----	------	------------

PRODUCT NUMBER:	T02
PRODUCT NAME:	White Diamond Pearl
DATE PREPARED:	4/1/2022
REVISION DATE:	11/8/2022
COMPANY:	Automotive Systems Warehouse
ADDRESS:	2330 Wildwood Rd.
CITY:	Wildwood, PA 15091
PHONE:	(412) 487-4800
EMERGENCY PHONE:	CHEMTREC: 1-800-424-9300

SECTION II - HAZARDOUS IDENTIFICATION

CLASSIFICATION:	
Flammable Liquids	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2B
Acute Toxicity, Inhalation	Category 4
Specific target organ toxicity, single exposure, R	Category 3
Germ Cell Mutagenicity	Category 2
Carcinogenicity	Category 1A, 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity, repeated exposure	Category 2

SIGNAL WORD: DANGER!

PICTOGRAMS:

HAZARD STATEMENTS: H226 Flammable liquid and vapor H315 Causes skin irritation H320 Causes eye irritation Harmful if inhaled H332 H335 May cause respiratory irritation Suspected of causing genetic defects H341 H350 May cause cancer Suspected of damaging fertility or the unborn child H361 Causes damage to organs through prolonged or repeated exposure H373 PRECAUTIONARY STATEMENTS: P201 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. P202 Keep away from heat/sparks/open flames/hot surface - No smoking. P210 Keep container tightly closed. P233 Ground/bond container and receiving equipment. P240 Use explosion-proof electrical/ventilating/light/equipment, etc. P241 Use only non-sparking tools. P242 P243 Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. P260 P261 Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. P264 Use only outdoors or in a well-ventilated are. P271 P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. IF ON SKIN: Wash with soap and water. P302+352 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for **PRODUCT NUMBER:** T02 **PRODUCT NAME:** White Diamond Pearl

P305+351+338	breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if
P308+313 P312 P314 P332+313 P337+313 P362 P370+378 P403+233 P403+235 P405	present and easy to do so - continue rinsing. IF exposed or concerned: get medical advice/attention. Call a POISON CENTER or a doctor/physician if you feel unwell. Get medical advice/attention if you feel unwell. If skin irritation occurs: get medical advice/attention. If eye irritation persists get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction. Store in a well ventilated place. Keep container tightly closed. Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

MATERIAL:	CAS #:	WEIGHT %:
Isopropyl Alcohol 99%	67-63-0	1-5
Butyl Acetate	123-86-4	35-40
Dimethylbenzene	1330-20-7	25-30

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION IV - FIRST AID MEASURES

CONTACT WITH EYES: Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

SKIN CONTACT: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

INGESTION: If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water fog, foam, dry chemical, or carbon dioxide extinguisher.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

UNUSUAL FIRE FIGHTING HAZARDS: Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Keep all sources of ignition and hot metal surfaces away from spill or release.

ENVIRONMENTAL PRECAUTIONS: Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

METHODS FOR CLEANING UP: Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851) for additional information.

SAFETY DATA SHEET

PRODUCT NUMBER: T02 **PRODUCT NAME:** White Diamond Pearl

HANDLING AND STORAGE: "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

CAS #:	OSHA PEL:	ACGIH TLV:
67-63-0	400ppm	200ppm (TWA)
123-86-4	150 ppm	150 ppm
1330-20-7	100ppm	100ppm
	67-63-0 123-86-4	67-63-0 400ppm 123-86-4 150 ppm

ENGINEERING CONTROLS: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

MONITORING: Follow accepted work practices for handling a flammable material.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE PROTECTION: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

SKIN PROTECTION: Impervious solvent resistent gloves. Impervious apron and work boots recommend where splashing may occur.

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas & vapors or air supplied respirator if necessary in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: ODOR: ODOR THRESHOLD: pH@25°C: MELTING/FREEZING POINT: FLASHPOINT: SPECIFIC GRAVITY (water=1): WATER SOLUBILITY: AUTO-IGNITION TEMPERATURE: DECOMPOSITION TEMPERATURE: BOILING RANGE: EVAPORATION RATE: LOWER FLAMMABLE LIMIT: UPPER FLAMMABLE LIMIT: WADOB DESEGUEST	White Mild Not Available Not Applicable Not Available .91 Negligible Not Available Not Available -°F Slower than Ether 1% 7%
LOWER FLAMMABLE LIMIT:	1%
VAPOR DENSITY (air=1): VISCOSITY: VOC AS PACKAGED: VOC REGULATORY:	>1.0 Not Available 6.20 6.23

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions of storage and handling.

CONDITIONS TO AVOID: Heat, open flames, ignition sources, electrical or static discharge.

HAZARDOUS DECOMPOSITION/BYPRODUCTS: CO2 and possibly CO and carbon smoke.

HAZARDOUS POLYMERIZATION: Will not occur.

POLYMERIZATION CONDITIONS TO AVOID: None.

INCOMPATIBILITIES: None known.

SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE: Inhalation, eye contact, skin contact, ingestion.

PRODUCT NUMBER: T02 **PRODUCT NAME:** White Diamond Pearl

INHALATION: Anesthetic. Irritation of respiratory tract or acute nervous system depression. Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

EYE CONTACT: High vapor concentrations are irritating to the eyes.

SKIN CONTACT: Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

INGESTION: Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

TOXICITY: MATERIAL:	LD50:	LC50:
Isopropyl Alcohol 99%	Dermal: 16,400 mg/kg (rabbit) Oral: 5,840 mg/kg (rat)	Inhalation: 8 h 1,600 ppm (rat)
Butyl Acetate	Oral: 7,100 mg/kg (mouse)	Inhalation: 2,000 ppm (rat)
Dimethylbenzene	Dermal: 4,500 mg/kg (rabbit) Oral: 2,840 mg/kg (rat)	Inhalation: 4 h 6,350 mg/l (rat)

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section XI (Tocicological Information) for further data on the effects of this product's components on test animals.

MOBILITY: This material is a mobile liquid.

DEGRADABILITY: This product is completely biodegradable.

BIOACCUMULATION: This product does not accumulate or biomagnify in the environment.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Do not discharge into drains, surface water, or groundwater. Empty containers can retain product residue and vapor. Observe all precautions even when containers are empty. The use and processing of this product, or addition of other constituents, may cuase it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Dispose of or incinerate in accordance with all applicable local, state, and federal regulations at a RCRA licensed facility.

SECTION XIV - TRANSPORT INFORMATION

US GROUND (DOT) SHIPPING INFORMATION: UN NUMBER: UN1263 PROPER SHIPPING NAME: PAINT TRANSPORT HAZARD CLASS: 3 PACKAGING GROUP: II

OTHER SHIPPING INFORMATION: With inner packagings containing 5 liters (1.32 gallons) or less, this product may be shipped as Limited Quantity. Any containers containing more than 5 liters may be shipped as: UN1263, PAINT, 3, PG II.

SECTION XV - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: UNITED STATES INVENTORY (TSCA 8b): All components are listed or exempted.

SARA TITLE III ACUTE: Yes	SECTION 311/312 HAZA CHRONIC: NO	ARD CATEGORIZATION: FIRE: Yes	PRESSURE : No	REAC ⁻ No	TIVE:
SARA TITLE III COMPONENT NAME Butyl Acetate Dimethylbenzen	-	R INFORMATION:		CAS #: 123-86-4 1330-20-7	% BY WT. 35-40 25-30

PRODUCT NUMBER: T02 **PRODUCT NAME:** White Diamond Pearl

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:			
COMPONENT NAME:	CAS #:	% BY WT.	RQ(LBS.)
Butyl Acetate	123-86-4	35-40	5000
Dimethylbenzene	1330-20-7	25-30	100

CALIFORNIA PROPOSITION 65: WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

CANADA:

All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

		SECTION XVI - OTHER INFORMATION
HMIS Health: HMIS Flammability: HMIS Reactivity:	2 3 0	

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.