

OSHA Hazard Communication Standard 29 CFR 1900.1200
Prepared to GHS Rev. 4



**SAFETY
DATA SHEET**

SECTION 1- CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: SUR-885

Product Use: Paint /Coating Solvent/Diluent

Use Restrictions: For Industrial and Professional Use Only

Manufacturer: Southeastern Chemical Industries Group LLC
660 Oak Place
Port Orange, FL 32127
386-760-9332

Transportation Emergency: 800-535-5053 (INFOTRAC)

SECTION 2- HAZARDS IDENTIFICATION

1) GHS Classification of the substance or mixture:

- Acute toxicity, Inhalation- Category 3
- Acute toxicity, Dermal- Category 3
- Acute toxicity, Oral- Category 3
- Acute toxicity, Eye- Category 2A
- Flammable Liquids- Category 2
- Specific target organ toxicity- single exposure- Category 3 (Central Nervous System)
- Aspiration Hazard – Category 2
- Reproductive toxicity – Category 2

2) Label Elements:



Signal Word: Danger

Hazard Statements:

- H225- Highly flammable liquid and vapor
- H301+H311+H331- Toxic if swallowed, in contact with skin or if inhaled
- H315+320- Causes skin irritation and eye irritation
- H370- Causes damage to organs

Precautionary Statements:

P102- Keep out of reach of children
 P210- Keep away from heat/sparks/open flame
 P233+P234- Keep only in original container and keep container tightly closed
 P241+P242+P243- Use explosion proof electrical/ventilating/lighting equipment. Use only non sparking tools. Take precautionary measures against static discharge.
 P260- Do not breathe fume/mist/vapors/spray
 P262- Do not get in eyes, on skin, or on clothing
 P264- Wash skin thoroughly after handling
 P280- Wear solvent resistant protective gloves and splash proof eyewear
 P307+P311- If exposed: call POISON CENTER or doctor/physician

Response Statements:

P303+P353+P361+P363- IF ON SKIN (or hair): Rinse skin with water/shower. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.
 P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present, and easy to do so. Continue Rinsing.
 P304+P340+ IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P301+P310- IF SWALLOWED: Immediately call POISON CENTER or doctor/physician.

Storage and Disposal Statements:

P233+P235+P403- Keep container tightly closed, keep cool and store in a well-ventilated place.
 P405- Store locked up.
 P501- Dispose of contents/container in accordance with local/regional/national regulation.

Other Hazards:

OSHA HCS 2012- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

HMIS Classification:

Health Hazard- 2
 Flammability- 3
 Physical Hazards- 0

NFPA Classification

Health Hazard - 2
 Flammability - 3
 Reactivity - 0

SECTION 3- COMPOSITION/INFORMATION ON INGREDIENTS

Chemical/Common Name	CAS #	PERCENTAGE	HAZARDOUS
N-butanol	71-36-3	1-5%	Yes
Toluene	108-88-3	35-40%	Yes
Methyl Ethyl Ketone	78-93-3	20-25%	Yes
Light Aliphatic Solvent	64742-49-0	15-20%	Yes
Ethylene Glycol Monobutyl Ether Acetate	112-07-2	5-10%	Yes

SECTION 4- FIRST AID MEASURES

Inhalation: If affected, remove individual to fresh air. If breathing is difficult administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet and obtain medical attention.
Skin: Immediately flush affected area with lots of water for at least 2 minutes. Remove contaminated clothing and wash before reuse.
Eyes: Flush immediately with large quantities of running water for at least 5 minutes. Obtain medical attention.

Ingestion: Immediately rinse mouth with a lot of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain immediate medical attention.

SECTION 5-FIRE FIGHTING MEASURES

Flash Point: 35°F (T.C.C.)

Auto-ignition Temperature: N/D

Lower Explosive Limit: N/D

Upper Explosive Limit: N/D

General Hazards-

Fire: Product is flammable or combustible in presence of ignition source.

Suitable Extinguishing Media: Use water spray, alcohol resistant foam, dry chemical or carbon dioxide. Treat as Class B (flammable liquid) fire.

Fire Fighting Procedures: Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous Combustion Products: Normal thermal hydrocarbon decomposition byproducts i.e. carbon oxides.

SECTION 6- ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing vapors, mist or gas.

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering.

Environmental precautions: Avoid run off to waterways and sewers.

Methods and material for containment and cleaning up: Stop leak if you can do it without risk.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste disposal container.

SECTION 7- HANDLING AND STORAGE

Precautions for safe handling:

Avoid contact with skin and eyes by wearing protective clothing and equipment. Avoid inhalation of vapor or mist. Use only with adequate ventilation.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place. Store away from acids, acidic materials and oxidizers. Do not store near heat or open flame.

SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters:

Component	CAS #	ACGIH Exposure Limits	OSHA Exposure Limits
N-butanol	71-36-3	20 ppm	100 ppm
Toluene	108-88-3	20 ppm	200 ppm
Methyl Ethyl Ketone	78-93-3	200 ppm	200 ppm
Light Aliphatic Solvent	64742-49-0	300 ppm	500 ppm
Ethylene Glycol	112-07-2	20 ppm	20 ppm
Monobutyl Ether Acetate			

Personal Protective Equipment-

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Hand protection: Wear protective gloves made from the following materials- nitrile rubber or polyethylene. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye Protection: Wear safety glasses with side shields.

Skin and Body Protection: Where extensive dermal exposure may be expected, either a chemical suit or chemical apron will be needed.

Hygienic Practices: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Products Description:	Clear liquid with characteristic odor
Solubility in Water:	Insoluble
Boiling Point:	approximately 75°F
Specific Gravity (WATER=1):	0.825
Vapor Pressure (mmHg):	N/D
Vapor Density (AIR=1):	>1
Evaporation Rate (BUTYL ACETATE=1):	>1
Flash Point (T.C.C.):	35°F
pH (1% w/w in water):	N/A

SECTION 10- STABILITY AND REACTIVITY DATA

Stability: Stable under recommended storage conditions.

Material to Avoid: Avoid contact with acids and strong oxidizers such as permanganate, chlorine, ect.

Conditions to Avoid: Keep away from heat, sparks and open flame.

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: May form carbon dioxide, carbon monoxide and various hydrocarbons.

SECTION 11- TOXICOLOGICAL INFORMATION

n-Butanol CAS No. 71-36-3

Acute oral toxicity- LD50 (Rat): 2,292 mg/kg

Acute dermal toxicity- LD50 (Rabbit): 3,430 mg/kg

Acute inhalation toxicity- LC50 (Rat, 4 h): 8,000 mg/

Repeated dose toxicity – No data available

Skin corrosion/irritation - No data available

Serious eye damage/eye irritation - No data available

Respiratory or skin sensitization - No data available

Carcinogenicity - No data available

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

U.S. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

U.S. OSHA Specifically Regulated Substances (29CFR 1910.1001-1050):

No carcinogenic components identified

Toluene CAS. No. 108-88-3

Acute oral toxicity- LD50 Oral: >5,580 mg/kg

Species: Male Rat

Acute inhalation toxicity- LC50: 28.1 mg/l

Species: Male & Female Rat

Remarks: Vapors may cause irritation to eyes and respiratory system.

Acute dermal toxicity- LD50: >5,000 mg/kg

Species: Rabbit

Remarks: May cause skin irritation in susceptible persons.

Methyl Ethyl Ketone CAS No. 78-93-3

Acute oral toxicity- LD50 2,737 mg/kg

Species: Rat

Symptoms: Tremors

Acute inhalation toxicity- LC50 320 mg/l

Species: Rat

Exposure time: 4 h

Acute dermal toxicity- LC50 6,480 mg/kg

Species: Rabbit

Exposure time: 24 h

Method: In vivo

Result: Mild skin irritation

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in desiccation of the skin.

Germ cell mutagenicity

Genotoxicity in vitro

Test type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: Negative

Test type: Mammalian cell gene mutation assay

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: Negative

Test type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: Negative

Genotoxicity in vivo

Test type: In vivo micronucleus test

Species: Mouse (male and female)

Dose: 1.96 ml/kg

Method: OECD Test Guideline 474

Result: Negative

Germ cell mutagenicity assessment: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity: Not classified as a human carcinogen.

Reproductive toxicity

Effects on fertility:

Species: Rat (female)

Application Route: Inhalation

Dose: 400, 1000, 3000 ppm

Frequency of Treatment: 7 d/wk

Maternal: NOAEC 1002 ppm

Teratogenic: NOAEC 1002 ppm

Method: OECD Test Guideline 414

Result: Did not show teratogenic effects in animal experiments

Light Aliphatic Naphtha – CAS No. 64742-49-0

Acute toxicity

Acute oral toxicity: LD50 (rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity: Remarks: No data available

Acute dermal toxicity: LD50 (rabbit, male and female): >2,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Skin corrosion/irritation

Species: rabbit

Result: Irritating to skin

Serious eye damage/eye irritation

Species: rabbit

Result: Irritating to eyes

Respiratory or skin sensitization

Test type: Buehler Tests

Species: guinea pig

Result: Did not cause sensitization on laboratory animals

Germ cell mutagenicity

Assessment: Mutagenicity classification not possible from current data

Carcinogenicity

Assesment: Not classifiable as a human carcinogen

Reproductive toxicity

Assessment: Fertility classification not possible from current data.

Embryotoxicity classification is not possible from current data.

STOT – single exposure

Exposure Route: Inhalation

Target Organs: Central Nervous System

Assessment: May cause drowsiness or dizziness. The substance of mixture is classified as specific target organ toxicant, single exposure, Category 3 with narcotic effects.

STOT – repeated exposure: No data available

Aspiration toxicity: May be fatal if swallowed and enters airways.

Further Information:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

Ethylene Glycol Monobutyl Ether Acetate – CAS No. 112-07-2

Acute oral toxicity: Acute toxicity estimate: 1,737 mg/kg
Method: Calculation Method
LD50 (rat, male and female): 1,800 mg/kg
Method: OECD Test Guideline 401
Assessment: The component mixture is moderately toxic after single ingestion.

Acute inhalation toxicity: Acute toxicity estimate: >30000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Acute dermal toxicity: Acute toxicity estimate: 1,479 mg/kg
Method: Calculation method

LD50 (rabbit): 1,500 mg/kg
Assessment: The component mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation Remarks: May cause skin irritation and/or dermatitis
Species: rabbit
Exposure time: 4 h
Result: No skin irritation

**Serious eye damage/
Eye irritation:** Vapors may cause irritation to the eyes, respiratory system and the skin.
Species: rabbit
Result: No eye irritation

Respiratory/skin irritation: Test Type: Buehler Test
Species: guinea pig
Result: Did not cause sensitization on laboratory animals.

Germ cell mutagenicity

Genotoxicity in vitro: Test type: Ames Test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: Negative
Remarks: Information given is based on data obtained from similar substances.

Genotoxicity in vivo: Test type: In vivo micronucleus test
Test species: mouse (male)
Application Route: Intraperitoneal
Exposure time: 3 d
Dose: 0 – 1100 mg/kg
Method: OECD Test Guideline 474
Result: negative
GLP: No data available

Germ cell mutagenicity: Assessment: Did not show mutagenic effects in animal experiments.

Carcinogenicity

Species: rat (male and female)
Application Route: inhalation (vapor)
Exposure time: 2 yrs
Dose: 0, 62.5, 125, 250 ppm
Frequency of Treatment: 6 h/d, 5 d/wk
NOAEL: 125
LOAEL: 250
Method: OECD Test Guideline 451

Carcinogenicity: Assessment: Carcinogenicity classification not possible from current data.

Result: Limited evidence of carcinogenic effects with no relevance to humans.

Carcinogenicity: Assessment: No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Effects on fertility: Test Type: Two-generation study
Species: mouse (male and female)
Application Route: oral
Dose: 0, 720, 1340, 2050, mg/kg bw

Frequency of Treatment: 7d/wk
General Toxicity – Parent: NOAEL: 720
General Toxicity F1: NOAEL: 720
Symptoms: Reduced fertility
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Effects on fetal Development:

Species: rabbit
Application Route: vapor
Dose: 0, 25, 50, 100, 200 ppm
Duration of Single Treatment: 13 d
Frequency of Treatment: 6 h/d
General Toxicity Maternal: NOAEC: 100 ppm
Teratogenicity: NOAEC: 200 ppm
Developmental Toxicity: NOAEC: 100 ppm
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

Species: rat
Dose: 0, 30, 100, 200, 300 mg/kg bw
Duration of Single Treatment: 3 d
General Toxicity Maternal: NOAEC: 30
Teratogenicity: NOAEC: >200
Developmental Toxicity: NOAEC: 100
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

Reproductive Toxicity: Assessment: No toxicity to reproduction. Did not show teratogenic effects in animal experiments.

STOT – Single Exposure: No data available

STOT – Repeated Exposure: No data available

Repeated dose toxicity: Species: rat (male and female)
NOAEL: <750
Application Route: Oral
Exposure time: 90 d
Number of exposures: 7 d/w
Dose: 750, 1500, 3000, 4500, 6000 ppm
Method: OECD Test Guideline 408
GLP: yes
Target Organs: Liver
Remarks: Information given is based on data obtained from similar substances.

Species: rabbit (male and female)
NOAEL: <400
Application Route: inhalation (vapor)
Exposure time: 4 wks
Number of Exposures: 4 h/d, 5 d/wk
Dose: 0, 400 ppm
Method: OECD Test Guideline 412
Target Organs: Kidney, blood

Species: rabbit (male and female)

NOAEL: >150 mg/kg
Application Route: Dermal
Exposure time: 90 d
Number of exposures: 5 d/wk
Dose: 0, 10, 50, 150 mg/kg bw

Aspiration toxicity: No aspiration toxicity classification

Further information: No data available

SECTION 12- ECOLOGICAL INFORMATION

n-butanol CAS No. 71-36-3

ECOTOXICITY-

Acute hazards to the aquatic environment:

Toxicity to fish: LC50 (Bluegill (*Lepomis macrochirus*), 24 h): >500 mg/l Mortality
LC50 (Fathead minnow (*Pimephales promelas*), 96 h): 1,630-1,840 mg/l
Mortality.

Toxicity to aquatic invertebrates: EC50 (Water flea (*Daphnia magna*), 48 h): 1,897 – 2,072
mg/l. Intoxication.

Chronic hazards to the aquatic environment:

Fish: No data available

Aquatic Invertebrates: No data available

Aquatic Plants: No data available

BIOACCUMULATIVE POTENTIAL

Bioconcentration Factor (BCF): Rainbow trout, Donaldson trout (*Oncorhynchus mykiss*), 0.38 (Static)
Rainbow trout, Donaldson trout (*Oncorhynchus mykiss*), 0.37 (Static)
Rainbow trout, Donaldson trout (*Oncorhynchus mykiss*), 0.39 (Static)
Rainbow trout, Donaldson trout (*Oncorhynchus mykiss*), 0.46 (Static)

Partition coefficient n-octanol/

Water (log KOW): Log Kow: 0.88

Methyl Ethyl Ketone - CAS#78-93-3:

ECOTOXICITY-

Toxicity to fish: LC50 (Fathead minnow): 2,993 mg/l
Exposure Time: 96 Hours

Toxicity to daphnia and other aquatic invertebrates: EC50 (Water flea): 308 mg/l
Exposure Time: 48 Hours
Test Type: Immobilization

Toxicity to algae: No data available

PERSISTENCE AND DEGRADABILITY-

Biodegradation: 198%

Biodegradability: Concentration: 2 mg/l

Result: readily biodegradable

GLP: yes

BIOACCUMULATIVE POTENTIAL-

Partition coefficient: log Pow- 2.49

Result: Readily biodegradable

Biodegradation: 98%
Exposure Time: 28 days
Test Substance: Methyl Ethyl Ketone
GLP: Yes

REGULATION/REMARKS-

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone, CAA Section 602 Class I Substances.

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A+B).

Toluene- CAS#108-88-3:

ECOTOXICITY-

Toxicity to fish: LC50 (Coho Salmon): 5.5 mg/l

Exposure Time: 96 Hours

Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates: EC50 (Ceriodaphnia dubia): 3.78 mg/l

Exposure Time: 48 Hours

Test Type: renewal

Toxicity to algae: EC50 (fresh water algae): 134 mg/l

Exposure Time: 3 Hours

Test Type: static test

Toxicity to bacteria: IC50 (bacteria): 84 mg/l

Exposure Time: 24 Hours

Test Type: static test

PERSISTENCE AND DEGRADABILITY-

Biodegradability: Inoculum- Sewage

Biodegradation: 100%

Remarks: Readily biodegradable

BIOACCUMULATIVE POTENTIAL-

Partition coefficient: log Pow- 2.73

REGULATION/REMARKS-

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone, CAA Section 602 Class I Substances.

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A+B).

Light Aliphatic Naphtha- CAS No. 64742-49-0:

Ecotoxicity

Toxicity to fish: LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l

Exposure time: 96 h

Toxicity to daphnia & other

Aquatic invertebrates: EC50 (Daphnia magna (water flea)) : 4.5 mg/l

Exposure time: 48 h

Toxicity to algae: EC50 (Pseudokirchneriella subcapitata (green algae)): 3.71 mg/l

Exposure time: 96 h

Ecotoxicity Assessment

Acute aquatic toxicity: Toxic to aquatic life

Chronic aquatic toxicity: Toxic to aquatic life with long lasting effects

Persistence and degradability:

Biodegradability: aerobic

Inoculum: activated sludge

Concentration: 20 mg/l

Biodegradation: 74.30%

Exposure time: 56 d

GLP: yes

Remarks: Inherently biodegradable

Bioaccumulative potential:

Partition coefficient: n-octanol/water

Remarks: No data available

Regulation: 40 CFR Protection of Environment: Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class I Substances.

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App. A + B).

Additional ecological

Information: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

Ethylene glycol monobutyl ether acetate CAS No 112-07-2

ECOTOXICITY-

Toxicity to fish: LC50 (Oncorhynchus mykiss (rainbow trout)): 28 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and Other aquatic invertebrates: (Water flea (Daphnia magna)): 37 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae: (Pseudokirchneriella subcapitata (green algae)): 520 mg/l
End point: Biomass
Exposure time: 72 h
Test Type: static test
Method: ISO 8692

Toxicity to bacteria: (Bacteria): 2,800 mg/l
Exposure time: 18 h
Test Type: growth inhibition

PERSISTENCE and DEGRADABILITY

Biodegradability: Result: Readily biodegradable
Biodegradation: 88%
Exposure time: 28 d
Method: OECD Test Guideline 301C

Theoretical Oxygen Demand (ThOD): 0.00210 mg/g
Method: OECD Test Guideline 301B

BIOACCUMULATIVE POTENTIAL

<u>Bioaccumulation:</u>	Bio concentration factor (BCF) : <100 Remarks: The substance has low potential for bioaccumulation.
Partition coefficient: n-octanol/ Water:	Log Pow: 0.83
Mobility in soil:	No data available
Other adverse effects:	No data available
Regulation:	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class I Substances.
Remarks:	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App A + B).
Additional ecological Information:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

SECTION 13- DISPOSAL CONSIDERATIONS

Further information: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of as hazardous waste in compliance with local and national regulations.

SECTION 14- TRANSPORT INFORMATION

Transport in accordance with all federal, state and local regulations.

DOT-

UN Number: UN 1263
UN proper shipping name: Paint related material (butanol, aromatic & aliphatic solvent, methyl ethyl ketone, ethylene glycol mono butyl ether acetate)
Hazard class: 3
Packing group: II

SECTION 15- REGULATORY INFORMATION

OSHA Hazards: Flammable liquid. Moderate skin & eye irritant.

SARA 302 Components: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304: Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a Section 304 EHS reportable quantity.

SARA 311/312 Hazards: Fire hazard, Acute health hazard, Chronic health hazard

Massachusetts Right to Know Components:

Product	CAS No.
Methyl Ethyl Ketone	78-93-3
Light aliphatic naphtha	64742-49-0
n-Butanol	71-36-3
Toluene	108-88-3
Ethylene Glycol Monobutyl Ether Acetate	112-07-2

Pennsylvania Right to Know Components:

Product	CAS No.
Methyl Ethyl Ketone	78-93-3
Light aliphatic naphtha	64742-49-0
n-Butanol	71-36-3
Toluene	108-88-3
Ethylene Glycol Monobutyl Ether Acetate	112-07-2

New Jersey Right to Know Components:

Product	CAS No.
Methyl Ethyl Ketone	78-93-3
Light aliphatic naphtha	64742-49-0
n-Butanol	71-36-3
Toluene	108-88-3
Ethylene Glycol Monobutyl Ether Acetate	112-07-2

California Prop. 65 Components: WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SECTION 16- OTHER INFORMATION

References: Not available

Other Special Considerations: Not available

Created: 05/08/2015

Last Updated: 02/01/2016

DISCLAIMER:

The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable. Information is correct to the best of our knowledge at the date of the MSDS publication.